

## 2025 Goorhand Paint

### 1. Storage of Paint:

- The paint must be stored in an insulated shed with temperatures between **5°C and 35°C**.
- Ensure that the paint is kept at a **minimum of 10°C** before applying it to the roof. Additionally, the paint should be stored at this temperature **24 hours prior to use**.

### 2. Handling and Application:

- Apply the product **only using a roller or brush. Do not use spray systems** or attempt to spray the product onto the roof under any circumstances.
- It is highly recommended that only the amount of paint needed for the next **60 minutes** of work be taken out.
- After use, ensure that the original container is **closed airtight** immediately to prevent the paint from drying out.
- You might find that you have to remix the paint again before taking more to continue recoating.
- Avoid storing the paint in direct sunlight, as exposure can cause the paint in buckets to cure prematurely, leading to lumps and drying out.

Attached to this email is the **Goorhand data sheet**, which contains more detailed information. Please make sure to read and follow these instructions carefully.

Additionally, I would like to address some important points regarding the **recoating process for roofs**:

- When recoating a roof, ensure that **one full day** is dedicated to cleaning the roof and removing any loose paint from the slates.
- It is **essential not to paint the roof on the same day** as cleaning, as the roof needs to be fully dry. Return to recoat the roof on **the next day** (if possible) once it has completely dried and there has been no rainfall overnight. This ensures that the paint adheres properly to the slates.
- **Two coats** of paint must be applied to the roof, but please ensure that the first coat has fully dried before applying the second.

Your sincerely

**Etex Ireland Ltd**