

Rotary Hammer LXT®

DHR202Z

18V • SDS-Plus • 20 mm • 2.0 J

Professional three-mode rotary hammer

An efficient rotary hammer for SDS-Plus bits with an anti-vibration handle. Suitable for impact and unstressed drilling, plus chipping. Speed range of 0 – 1 100 min⁻¹. Impact energy of 2.0 J and max. drilling capacity of 20 mm in concrete. Tool only, battery and charger not included.



Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	18 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	0 - 1100 min ⁻¹
Impacts per Minute (IPM)	0 - 4000 min ⁻¹
Max. Drilling Diameter in Wood	26 mm
Max. Drilling Diameter in Concrete	20 mm
Max. Drilling Diameter in Steel	13 mm
Optimum Drilling Diameter Range in Concrete	4 - 12 mm
Impact Energy	1,9 J
Drilling diameter with TCT core bit	54 mm
Adapted for SDS-PLUS bits	✓
Electronic brake	✓
Sound Power Level (L _{WA})	99 dB(A)

User benefits

- Battery protection system automatically shuts off power when the battery level is low
- LED light illuminates the work site
- 3-Mode operation for "Rotation Only", "Hammering with Rotation" or "Hammering Only" for multiple applications
- Reversing switch
- Reversing switch is conveniently located
- Compact and lightweight for reduced operator fatigue
- One touch sliding chuck enables quick and easy bit changes

EAN 0088381658119

Link to product - www.makita.com



Related products

Standard AC

324219-0
Depth Gauge

Optional AC

193472-7
Dust extraction set Ø 25 / 31 mm



821551-8
Makpac case (3)



837634-4
MakPac (3) Inlay



D-16368
Chisel set SDS-PLUS, 5 pcs



D-74136
Drill Bit Set T.C.T, SDS-PLUS, 4 pcs



Other

[User manual](#)

[Parts drawing](#)